









ME 67 Back-Electret Microphone Head

The ME 67 is a long gun microphone head designed for use with the K6 and K6P powering modules. A highly directional microphone, it can be used where the microphone must be placed at a distance from the sound source.

Features—Benefits

- · Lobar pick-up pattern
- · Highly directional
- · Very low inherent self-noise
- · High sensitivity factor
- · Wide frequency response

Technical Data

Pick-up pattern lobar (long gun) Frequency response $40-20,000~Hz \pm 2.5~dB$ Sensitivity (free field, no load) (1 kHz) $50~mV/Pa \pm 2.5~dB$ Nominal impedance $200~\Omega$ (with K6) Min. terminating impedance $1000~\Omega$ (with K6)

Equivalent noise level

A-weighted (DIN IEC 651) 10 dB CCIR-weighted (CCIR 468-3) 21 dB

Max. SPL (1 kHz) 125 dB (THD = 1 %)

Dimensions in inches .88 x 13.5 Weight 3.52 oz

Optional Accessories

Foam windshield MZW 67 Pro
Shockmount kit MZS 20-1
Blimp windscreen MZW 70-1
Longhair windcoat MZH 70-1

Architect's Specifications

Lobar (long gun) microphone head suitable for K6 and K6P powering modules. Frequency response 50 Hz–20,000 Hz \pm 2.5 dB, sensitivity (free field, no load) 50 mV/Pa \pm 2.5 dB at 1 kHz, nominal impedance 200 Ω (with K6), min. terminating impedance 1000 Ω (with K6), equivalent noise level A-weighted 10 dB, CCIR-weighted 21 dB, max. SPL 125 dB at 1 kHz (THD = 1 %), dimensions .88 x 13.5 inches, weight 3.52 oz.

Sennheiser Electronic Corporation, 1 Enterprise Drive, Old Lyme, CT 06371
Telephone: 860-434-9190 • Fax: 860-434-1759 • Web: http://www.sennheiserusa.com
Sennheiser Mexico: Av. Xola 613, PH6, Col. Del Valle 03100, Mexico, DF. Telephone: (525) 639-0956. Fax: (525) 639-9482
Sennheiser Canada: 221 Labrosse Ave, Pte-Claire, PQ H9R 1A3. Telephone: 514-426-3013. Fax: 514-426-3953
Manufacturing Plant: Am Labor 1, 30900 Wedemark, Germany