

## Masonry Analysis and Design Homework 1

$f'_m = 1500$   
 GR40  
 Med wt units w/ 10% of grout  
 $f'_m = 1500$   
 GR40 steel  
 grout solid


1. A solid grouted 8-in concrete masonry beam is reinforced with two #4 reinforcing bars and has an effective depth of 32.5 inches. Determine the allowable moment. What is the allowable load if the effective span is 10.67 ft?
2. A 10-in.-wide simply-supported brick lintel with a span of 15 feet is to carry a service load of 875 lb/ft, not including its own weight. The overall depth of the beam is 36 in. The flexural reinforcement consists of two #5 bars. Determine the allowable moment for the beam. Is the beam safe?
3. A retaining wall is to be made of 12" unreinforced CMU. Determine if the wall is sufficient.

$f'_m = 1,500$  psi                      Weight of masonry (12-in. thick - solid grouted) = 100 psf  
 Type N mortar (PCL)                      Running bond  
 Weight of soil  $\gamma = 100$  pcf                      Active earth pressure coefficient  $K = \frac{1}{3}$



---

<b>Calculations and Discussion</b>	<b>Code Reference</b>
------------------------------------	-----------------------

---



MASOURY




$f'_m = 1500 \text{ psi}$   
 GR40 STEEL  
 MEDIUM WT UNIT  
 w/ 140 pcf grouted  
 SOLID

$n A_s = \frac{29000000}{1.35(10)^6} \cdot 0.4 = 21.5(.4)$   
 $= 8.6 \text{ in}^2$

$$\frac{7.63(kd)^2}{2} = 8.6(32.5 - kd)$$

$$kd^2 3.815 + 8.6 kd - 279.5 = 0 \quad kd = 7.51''$$



$$M = C \left( d - \frac{kd}{3} \right)$$

$$= \frac{1}{2} (7.51)(500)(7.63) \left( 32.5 - \frac{7.51}{3} \right)$$

$$= 35810 \text{ ft-lb}$$

(COMPRESSION CONTROLLED)

$$M = T \left( d - \frac{kd}{3} \right)$$

$$= .4(20000) \left( 32.5 - \frac{7.51}{3} \right)$$

$$= \underline{\underline{20000 \text{ ft-lb}}}$$

TENSION IN THE STEEL  
 CONTROL

$$\begin{aligned} \text{WT OF BEAM} &= 78 \text{ psf} \\ &= 78 \text{ psf} \left( \frac{36}{12} \right) = 234 \text{ lb/ft} \end{aligned}$$

(36" TOTAL BEAM HEIGHT ESTIMATED)

$$M = 20000 \text{ ft-lb} = \frac{(234 + W)(10.67)^2}{8}$$


$$W = \frac{1171}{1171} \text{ lb/ft} \quad \text{ALLOWABLE LOAD}$$

2. 10" WIDE BEAM,

$f'_m = 1500 \text{ psi}$   
GR 40 STEEL

MEDIUM WT FULLY GROUTED @ 140 pcf  $E_m$

\* NOTE: SOLVED AS  
CONCRETE MASONRY.  
PROBLEM IS  
ACTUALLY CLAY  
WHICH EFFECTS



$$A_s = 2\#5 = 0.61 \text{ in}^2$$

$$n = 21.5$$

$$\frac{9.63(d)^2}{2} = 13.12 \text{ in}^2 (32.5 - d)$$

$$4.815(d)^2 + 13.12d - 426.4 = 0$$

$$d = 8.15''$$

M BASED ON COMPRESSION FAILURE

$$M = \frac{1}{2} (500 \text{ psi}) (8.15) (9.63) \left( 32.5 - \frac{8.15}{3} \right) \frac{1 \text{ ft}}{12''}$$

$$= 48700 \text{ ft-lb}$$

M BASED TENSION IN THE STEEL


$$M = (0.61 \text{ in}^2 (20000 \text{ psi})) \left( 32.5 - \frac{8.15}{3} \right) \frac{1}{12} = 30280 \text{ ft-lb}$$

$$\text{WT OF WALL} = 98 \text{ lb/ft}^2 (36/12) = 294 \text{ lb/ft}$$

$$M = \left( \frac{875 + 294}{8} \right) (15)^2 = 32878 \text{ ft-lb} > 30280 \text{ ft-lb}$$

BEAM FAILS.

3.



$$M = \frac{1}{2} \left( 200 \frac{\text{lb}}{\text{ft}^2} \right) (6') (1') (2')$$

$$= 1200 \text{ ft-lb / ft}$$

$$V = 600 \text{ lb}$$

$$f_{mt} = \frac{M}{S} = \frac{1200 \text{ ft-lb} (12''/\text{ft})}{270 \text{ in}^3} = 53.3 \text{ psi} < 63 \text{ psi}$$

$$f_v = \frac{VQ}{Ib} =$$

$$= \frac{3}{2} \frac{V}{A} \quad \text{FOR RECT. SECTION}$$

$$= \frac{3}{2} \left( \frac{600 \text{ lb}}{140 \text{ in}^2} \right) = 6.42 \text{ psi} < 1.5 \sqrt{1500} = 58 \text{ psi}$$

$$< 120 \text{ psi}$$

$$< 60 + \frac{N_v}{A_n}$$

$$60 + \frac{100 \text{ psf} (6' \times 1')}{140}$$

$$= 64.3 \text{ psi}$$

SHEAR & MOMENT ARE O.K.